



## SATURN UPE Ω/T SD

### EN 12115

**Rubber chemical suction and delivery hose acc. to EN12115.**

Suitable for a very large number of chemicals such as most industrial acids, lyes and alkalis, and mineral oil products and solvents. Also suitable for all foods including animal and vegetable fats. Thanks to the black UPE, the inner wall of the hose is conductive.

\* Temperature up to +100° C, depending on medium

Cover	EPDM
Tube	UHMWPE
Material inlay(s)	Textile
Static wire	Yes
Number of reinforcement(s)	2
Colour cover	Black
Colour tube	Black
Spiral	Yes
Electrically conductive tube	R < 10 <sup>6</sup> Ω
Electrically conductive cover	R < 10 <sup>6</sup> Ω
Norm	EN 12115

Article nr.	I.D. mm	U.D. mm	W.D. Bar	B.D. Bar	Vacuum %	Temp.	B.R. mm	Length mtr.	Weight gr/mtr
1401554	50	66	16	64	90	-35 - +100°C*	413	40	1820
1401556	75	91	16	64	80	-35 - +100°C*	525	40	2880
1401557	100	116	16	64	80	-35 - +100°C*	675	20	3870
1401560	152	172	16	64	80	-35 - +100°C*	1014	61	8320