



## MERCUR SPIR Ω/T SD

### EN 12115

#### Rubber oil and petrol resistant suction and delivery hose

Rubber oil- and petrol resistant suction and delivery hose according to EN 12115. Suitable for transporting hydrocarbons with an aromatic content not exceeding 50%. Ideal for transporting gasoline and diesel from tank to tank and tank to petrol stations.

#### **Electrical properties:**

Type Ω/T according to EN 12115 (R<106 Ω, R<109 Ω through the wall)

Cover	CR
Tube	NBR
Material inlay(s)	Textile
Static wire	Yes
Number of reinforcement(s)	2
Colour cover	Black
Colour tube	Black
Spiral	Yes
Electrically conductive tube	R < 10 <sup>6</sup> Ω
Electrically conductive cover	Yes
Norm	EN 12115:2011 TRbF 131 deel 2 par. 5.5 EN 1761

Article nr.	I.D. mm	U.D. mm	W.D. Bar	B.D. Bar	Vacuum %	Temp.	B.R. mm	Length mtr.	Weight gr/mtr
1201440	19	31	16	64	90	-30 - +70°C	95	40	690
1201441	25	37	16	64	90	-30 - +70°C	150	40	840
1201442	32	44	16	64	90	-30 - +70°C	175	40	1030
1201443	38	51	16	64	90	-30 - +70°C	225	40	1180
1201444	51	67	16	64	90	-30 - +70°C	275	40	1790
1201445	63	79	16	64	90	-30 - +70°C	300	40	2330
1201446	76	92	16	64	90	-30 - +70°C	350	40	2820
1201447	102	118	16	64	90	-30 - +70°C	450	40	3820
1201449	152	170	16	64	80	-30 - +70°C	608	40	8320