



Compotec PTFE HEAVY DUTY PTFE SUCTION & DISCHARGE HOSE EN 13765:2010 TYPE 3

The superior chemically inert quality of Fluoropolymers, make COMPOTEC® PTFE hoses ideals for the transfer of a wide range of very hazardous chemicals. This univer-sal hose can help eliminate the costly redundancy of inventory to maintain the various hose constructions usually required.

Due to its special construction, the hose is very flexible and has a small bending radius.

Cover	Polyester/PVC and SS AISI-304 wire
Tube	PTFE lining and SS AISI-316 wire
Colour cover	Red
Maximum working pressure	16 bar
Temperature range	-40°C/+100°C
Norm	EN 13765:2015 Type 3 Hose is approved by Lloyds register of Shipping

Size		Maximum working pressure			bend radius		weight	length	
mm	Inch	Bar	P.S.I.		mm	Inch	Kg. / mt	Mt.	Feet
50	2"	15	200	5:1	180	7	2,04	40	132
100	4"	15	200	5:1	400	16	4,74	40	132
150	6"	15	200	5:1	550	22	10,50	40	132
200	8"	15	200	5:1	800	32	12,85	40	132
250	10"	15	200	5:1	1000	40	20,96	25	82
300	12"	15	200	5:1	1200	48	31,69	25	82