



## Compotec Oil 800 HEAVY DUTY HYDROCARBON SUCTION & DISCHARGE HOSE EN 13765:2010 TYPE 3

Specially designed for loading and unloading oil and fuel on tank trucks with an aromatic content up to 100%. Due to its special construction with 1 galvanised spiral inside and one stainless steel spiral outside (stainless steel on demand), the hose is very flexible and has a very small bending radius.

\* Temperature up to +100° C, depending on medium

<b>Static wire</b>	2
<b>Number of reinforcement(s)</b>	Blue Black
<b>Colour cover</b>	Yes
<b>Colour tube</b>	
<b>Spiral</b>	-40 - +100°C
<b>Temperature</b>	
<b>Norm</b>	EN ISO 1402 (BS 5173 section 102.10:1990).

Size		Maximum working pressure		bend radius		weight	length	
mm	Inch	Bar	P.S.I.	mm	Inch	Kg. / mt	Mt.	Feet
50	2"	15	200	180	7	2,18	40	132
100	4"	15	200	400	16	5,28	40	132
150	6"	15	200	575	23	11,90	40	132
200	8"	15	200	800	32	15,65	40	132
250	10"	15	200	1000	40	22,53	25	82
300	12"	15	200	1200	48	31,78	25	82